

# Kullanıcılara ait ekstra bilgileri nasıl saklarım?

IDM kullanıcılarla ilgili bir takım verileri de beraberinde saklamaktadır. Ancak bu veriler sizin uygulamanız için yeterli olmayabilir, bu durumda IDM’de üretilen her bir kullanıcı için ekstra JSON veri tipinde veri saklamanıza olanak sağlamaktadır. Bu verileri aşağıdaki api ucu vasıtası ile kaydedebilir ve sorgulayabilirsiniz.

- AddOrUpdateUserExtraData api ucu sayesinde bir kullanıcınız için tutmak istediğiniz ekstra verileri kaydedebilirsiniz.

**POST** `/api/users/{id}/data/appid={appid}` Add or update user extra data **AddOrUpdateUserExtraData**

Adds or updates the custom data field of specified user and app

**Parameters** Cancel

Name	Description
<b>id</b> * required string (path)	User ID to upsert extra data <input type="text" value="id - User ID to upsert extra data"/>
<b>appid</b> * required string (path)	App ID to upsert extra data <input type="text" value="appid - App ID to upsert extra data"/>
request (body)	UserId, appid and extra data <div><b>Example Value</b>   <b>Model</b><pre>{  "ExtraData": "string"}</pre></div>

Örnek

```
curl --location --request POST 'http://<idmapiadresi>/api/users/<userId>/data/appid=<appId>' \
--header 'client_id: <clientId>' \
--header 'client_secret: <clientSecret>' \
--header 'Content-Type: application/json-patch+json' \
--data-raw '{
  "ExtraData": " {\\\\"UserTypeId\\\\":\\"2\\\\",\\"Code\\\\":\\"TestCode\\\\",\\"DefaultCustomerId\\\\":\\"15\\\\"} "
}'
```

- Benzer şekilde kaydedilen extra veriler aşağıdaki api ucu yardımı ile sorgulanabilmektedir.

**GET** /api/users/{id}/data/appid={appid} Get user extra data GetUserExtraData

Retrieves the custom data field of specified user and app

**Parameters** Cancel

Name	Description
<b>id</b> * required string (path)	User ID to get extra data id - User ID to get extra data
<b>appid</b> * required string (path)	App ID to get extra data appid - App ID to get extra data
<b>client_id</b> * required (header)	Security Info Client ID UID value client_id - Security Info Client ID UID value
<b>client_secret</b> * required (header)	Security Info Client Secret UID value client_secret - Security Info Client Secret UIC

Örnek

```
curl --location --request GET 'http://<idmapiadresi>/api/users/<userid>/data/appid=<appId>' \
--header 'client_secret: <client_id>' \
--header 'client_id: <client_secret>'
```